

# CLEANLINE - LAVENDER POLISH AEROSOL

## 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Name CLEANLINE - LAVENDER POLISH AEROSOL

Supplier : **Prime Source**

PO Box 15247  
Birmingham  
B22 3HN

**Tel : 0121 328 6740**

**Email : Info@prime-source.co.uk**

## 2 HAZARDS IDENTIFICATION

R12 Extremely flammable.

PRESSURISED CONTAINER - increase in temperature to greater than 50C will cause internal pressure to rise potentially causing bursting/explosion.

Classification F+;R12.

## 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EINICS No.	CAS No.	Content	Classification
ALIPHATIC DISTILLATE	265-150-3	64742-48-9	5 - 10%	Xn;R65. R10,R66.
BUTANE	203-448-7	106-97-8	10 - 30%	F+;R12
KEROSENE - NARROW CUT - NON AROMATIC		64742-47-8	5 - 10%	Xn;R65. R66.

The Full Text for all R-Phrases are Displayed in Section 16

## 4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once., Keep the affected person warm and at rest. Get prompt medical attention., For breathing difficulties oxygen may be necessary.

INGESTION

Rinse mouth thoroughly., Drink plenty of water., Get medical attention.

SKIN CONTACT

Wash the skin immediately with soap and water., Get medical attention if any discomfort continues.

EYE CONTACT

Promptly wash eyes with plenty of water while lifting the eye lids., Continue to rinse for at least 15 minutes., Get medical attention if any discomfort continues.

## 5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use:, Powder., Dry chemicals, sand, dolomite etc., Water spray, fog or mist.

SPECIAL FIRE FIGHTING PROCEDURES

Containers close to fire should be removed or cooled with water., Use water to keep fire exposed containers cool and disperse vapours.

UNUSUAL FIRE & EXPLOSION HAZARDS

Aerosol cans may explode in a fire.

## 6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear necessary protective equipment., Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate., If leakage cannot be stopped, evacuate area.

ENVIRONMENTAL PRECAUTIONS

Any spillage needs to be contained and not allowed to enter water courses

## 7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame., Avoid spilling, skin and eye contact., Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

USAGE DESCRIPTION

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs	STEL - 15 min	Notes
BUTANE	WEL	600 ppm 1450 mg/m3	750 ppm 1810 mg/m3	

PROTECTIVE EQUIPMENT



HAND PROTECTION

For prolonged or repeated skin contact use suitable protective gloves.

EYE PROTECTION

Eye protection not normally required with day to day use of product

OTHER PROTECTION

General workwear only

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Aerosol

COLOUR	White
ODOUR	Strong fragrant (Leather/Lavender type)
PHYSICAL DATA COMMENTS	Information given relates to total aerosol container contents.
RELATIVE DENSITY	0.803 20
FLASH POINT (°C)	- 74 N/A.
AUTO IGNITION TEMPERATURE (°C)	+ 405
FLAMMABILITY LIMIT - LOWER(%)	1.8
FLAMMABILITY LIMIT - UPPER(%)	10.0

#### 10 STABILITY AND REACTIVITY

STABILITY	Stable under normal temperature conditions.
CONDITIONS TO AVOID	Avoid heat, flames and other sources of ignition., Increase in temperature to greater than 50 degrees will cause rise in internal pressure with likelihood of bursting/explosion.
HAZARDOUS DECOMPOSITION PRODUCTS	Fire creates:, Toxic gases/vapours/fumes of:, Carbon monoxide (CO)., Carbon dioxide (CO2).

#### 11 TOXICOLOGICAL INFORMATION

INHALATION	High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting., Gas or vapour displaces oxygen available for breathing (asphyxiant)., Unconsciousness.
SKIN CONTACT	No specific health warnings noted.
EYE CONTACT	Irritation of eyes and mucous membranes.

#### 12 ECOLOGICAL INFORMATION

ECOTOXICITY	Not classed as Hazardous to the Environment but release to the environment should be avoided.
-------------	---

#### 13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS	Empty containers must not be burned because of explosion hazard., Dispose of waste and residues in accordance with local authority requirements.
------------------	--

#### 14 TRANSPORT INFORMATION

UN NO. ROAD	1950
UK ROAD CLASS	-
ADR CLASS NO.	2.1
PROPER SHIPPING NAME	AEROSOLS, FLAMMABLE
UN NO. SEA	1950
IMDG CLASS	2.1
IMDG PACK GR.	N/A
UN NO. AIR	1950
AIR CLASS	2.1
AIR PACK GR.	N/A

#### 15 REGULATORY INFORMATION

##### LABELLING



RISK PHRASES	Extremely Flammable (F+) R12 Extremely flammable.
SAFETY PHRASES	S2 Keep out of the reach of children, S16 Keep away from sources of ignition - No smoking., S23 Do not breathe vapour/spray., S51 Use only in well-ventilated areas.
STATUTORY INSTRUMENTS	Control of Substances Hazardous to Health., Chemicals (Hazard Information and Packaging) Regulations.
APPROVED CODE OF PRACTICE	Classification and Labelling of Substances and Preparations Dangerous for Supply.
GUIDANCE NOTES	Workplace Exposure Limits EH40., Introduction to Local Exhaust Ventilation HS(G)37., CHIP for everyone HSG(108).

#### 16 OTHER INFORMATION

GENERAL INFORMATION	The following risk phrases relate to the raw materials in the product and not the product itself:-
REVISION DATE	05/04/2006
REV. NO./REPL. SDS GENERATED	13
RISK PHRASES IN FULL	R12 Extremely flammable.  R10 Flammable., R66 Repeated exposure may cause skin dryness or cracking., R65 Harmful: may cause lung damage if swallowed.  R66 Repeated exposure may cause skin dryness or cracking., R65 Harmful: may cause lung damage if swallowed.