## TECHNICAL CONCEPTS

The Neutralle Centre, Culley Court, Orton Southgate, Peterborough, Cambridgeshire, PE2 6WA.

Phone: +44 (0)870 568 6824 Fax: +44 (0)870 225 8390 E-mail: info@technical-concepts.co.uk Website www.technicalconcepts.co.uk



## SAFETY DATA SHEET

Page 1 of 5

# **Microburst Inspirations**

Revision

Revision date 30-Nov-2007

#### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name Microburst Inspirations

NEUTRALLE Metered aerosols - Air Neutralizers.

Intended use Fragranced metered aerosol space sprays designed for use in proprietary automated

dispensers.

Company Technical Concepts International Ltd

The Neutralle Centre

Culley Court Orton Southgate Peterborough PE2 6WA United Kingdom

www.technicalconcepts.co.uk

Telephone +44 (0)870 568 6824
Fax +44 (0)870 225 8390

Informing Department Technical Services Department.

## 2. COMPOSITION / INFORMATION ON INGREDIENTS

**Description** Mixture of organic solvents, perfume and propane/iso-butane (propellant)

### Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Ethanol	1-10%	64-17-5	200-578-6	F; R11
Isopropanol	1-10%	67-63-0	200-661-7	F; R11 Xi; R36 R67
(Propan-2-ol)				
Butylphenyl methylpropional	0-0.5%	80-54-6	201-289-8	Xn;R22 Xi;R43
Amyl Cinnamal	0-0.5%	122-40-7	204-541-5	Xi;R43 N;R51/53
1,1,6,7-tetramethyl-6-acetyldecalene	0-0.5%	54464-57-2	259-174-3	N;R51/53
4-tert-butyl-3,5-dinitro-2,6-dimethylacetophenone	1-10%	81-14-1	201-328-9	N; R50/53
Hexyl Cinnamal	0-0.5%	101-86-0	202-983-3	Xi; R43
2,4,6-trinitro-1,3-dimethyl-5-tert-butyl benzene	0-0.5%	81-15-2	201-329-4	
Benzyl salicylate	0-0.5%	118-58-1	204-262-9	Xi; R43 N; R51/53
Citronellol	0-0.5%	106-22-9	203-375-0	
Cinnamyl alcohol	0-0.5%	104-54-1	203-212-3	Xi; R43
Hydroxyisohexyl 3-cyclohexene carboxaldehyde	0-0.5%	31906-04-4	250-863-4	Xi; R43
Benzyl benzoate	0-0.5%	120-51-4	204-402-9	Xn; R22
Hexyl Salicylate	0-0.5%	6259-76-3	228-408-6	Xi;N

Additional Information: Full text for all Risk Phrases mentioned in this section are displayed in Section 16.

Print date 4-Dec-2007

Revision 8

Revision date 30-Nov-2007

3. HAZARDS IDENTIFICATION

Main hazards Extremely flammable.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

Classification system The classification is in line with current EC lists. It is expanded, however, by

information from technical literature and by information furnished by supplier

companies

4. FIRST AID MEASURES

Skin contact Remove contaminated clothing. Wash all contaminated clothing before reuse. Wash off

immediately with plenty of soap and water. Seek medical attention if irritation or

symptoms persist.

Eye contact Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek

medical attention if irritation or symptoms persist.

Inhalation Move the exposed person to fresh air. Seek medical attention if irritation or symptoms

persist.

Ingestion Rinse mouth thoroughly. DO NOT INDUCE VOMITING. Seek medical attention if

irritation or symptoms persist.

5. FIRE FIGHTING MEASURES

**Extinguishing media** Carbon dioxide (CO2) Alcohol resistant foam.

Do NOT use water jet.

Fire hazards carbon oxides may be formed in fire conditions.

Protective equipment Wear suitable protective clothing. Wear suitable protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Wear suitable protective equipment. Evacuate personnel to a safe area.

**Environmental precautions** No environmental requirements.

Clean up methods Ensure adequate ventilation. Absorb liquid components with

liquid binding material (sand, diatomite, acid binders, universal binders, sawdust).

7. HANDLING AND STORAGE

**Handling** Wear suitable protective equipment.

Storage Ensure adequate ventilation of the working area.

Keep in a cool, dry, well ventilated area.

Heat will increase pressure in sealed containers.

Keep away from sources of ignition - No smoking.

Pressurised container. Protect from sunlight and do not expose to temperatures

exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame

or any incandescent material.

Do not store with strong oxidising agents. Strong acids.

Protect from heat and direct sunlight.

Observe official regulations on storing packagings with pressurised containers.

Print date 4-Dec-2007

Revision date 30-Nov-2007

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **Exposure limits**

Ethanol WEL 8-hr limit ppm: 1000 WEL 8-hr limit ma/m3: 1920

WEL 15 min limit ppm: -WEL 15 min limit mg/m3: -

Isopropanol WEL 8-hr limit ppm: 400 WEL 8-hr limit mg/m3: 999 (Propan-2-ol) WEL 15 min limit ppm: 500 WEL 15 min limit mg/m3: 1250

**Engineering measures** Ensure adequate ventilation of the working area. The product does not contain any

relevant quantities of materials with critical values that have to be monitored at the

workplace.

Occupational exposure

Wash hands during breaks and at the end of the work.

controls

Respiratory protection Not required, but ensure adequate ventilation when using the product.

Hand protection Not required when used as directed. Wash hands after handling the product.

Eye protection Not required when used as directed. Protective equipment Not required when used as directed.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Description Aerosol.

Colour According to Product specification.

Odour Characteristic.

**Boiling point** Not applicable, as aerosol.

Flash point Not applicable, as aerosol.

**Explosive** 1.8 - 19.0 Vol % Vapour pressure 3.5 - 4.5 bar

Relative density 0.619 - 0.645 g/cm<sup>3</sup>

Melting point Not applicable, as aerosol.

Autoignition temperature Product is not self-igniting.

**Further information** Product is not explosive. However, formation of explosive air/steam mixtures is

possible

#### 10. STABILITY AND REACTIVITY

Stability Will not decompose if stored and used as recommended.

Conditions to avoid Keep away from sources of ignition - No smoking.

Protect from heat and direct sunlight.

Pressurised container. Protect from sunlight and do not expose to temperatures

exceeding 50 °C.

Materials to avoid Strong oxidising agents. Strong acids.

Hazardous decomposition carbon oxides may be formed in fire conditions.

products

## 11. TOXICOLOGICAL INFORMATION

Acute toxicity No data is available on this product.

Sensitization May cause sensitisation by skin contact.

Revision 8
Revision date 30-Nov-2007

12. ECOLOGICAL INFORMATION

**Ecotoxicity** No data is available on this product.

**Bioaccumulation** Does not bioaccumulate.

Further information Do not allow undiluted product or large quantities of it to reach ground water, water

bodies or sewage system.

13. DISPOSAL CONSIDERATIONS

**General information** Dispose of in compliance with all local and national regulations.

**Disposal of packaging**Dispose of in compliance with all local and national regulations.

14. TRANSPORT INFORMATION

ADR/RID

Proper Shipping AEROSOLS . UN 1950

Name

Packing group - Class 2

Hazard ID -

Remarks UN 1950 AEROSOLS should be placed inside the diamond shaped label.

Goods are classed as "Limited Quantities" and are therefore exempt from ADR

regulations. Check local local legislation for domestic transport.

**IMDG** 

UN 1950 Packing group -

Class 2 Marine pollutant NO

EmS Code F-D S-U

Remarks "Limited Quantity"

AEROSOLS is required according to IMDG regulations

.

IATA

UN 1950 Packing group -

Class 2 Subsidiary risk see SP63

Remarks "Limited Quantity".

Revision date 30-Nov-2007

15. REGULATORY INFORMATION

**Labelling** The product is classified in accordance with 67/548/EEC.

For professional use only.

Symbols F+ - Extremely flammable

**Risk phrases** R12 - Extremely flammable.

R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Safety phrases P10 - Contains hexyl Cinnamal, Amyl cinnamal, citronellol, benzyl salicylate, cinnamyl

Alcohol, hydroxyisohexyl 3-cyclohexene carboxaldehyde, butylphenyl methylpropional.

May produce an allergic reaction. S2 - Keep out of the reach of children.

S16 - Keep away from sources of ignition - No smoking.

S23 - Do not breathe gas/fumes/vapour/spray.

S51 - Use only in well-ventilated areas.

Further information Pressurised container: protect from sunlight and do not expose to temperatures

exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame

or any incandescent material.

### 16. OTHER INFORMATION

Text of risk phrases in

R11 - Highly flammable.

Section 2 R22 - Harmful if swallowed.

R36 - Irritating to eyes.

R43 - May cause sensitisation by skin contact.

R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R67 - Vapours may cause drowsiness and dizziness.

Informing Department Technical Services Department.

Mr. K. Anderson.

Data sources Raw Material Data Sheets.

EH40/2005 Occupational Exposure limits (UK)

Further information The information supplied in this Safety Data Sheet is designed only as guidance for the

safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other

process.

Print date 4-Dec-2007